

## Network Thermostats BACstat II: DNT-T103/H103B

### Description

The DNT-T103 is an intelligent room thermostat with a custom 3-value, 96 segment, LCD display. The DNT-T103 can communicate directly on a BACnet MS/TP network.

The DNT-T103 can display a wide-range of digital or analog values including setpoints, temperature, airflow, heating and cooling status, fan speed, valve and damper position, and more. When connected on a BACnet MS/TP network, the DNT-T103 functions as an independent BACnet thermostat. When connected to a Controller, on a LINKnet network, the DNT-T103 provides a programmable remote sensor and expanded I/O capabilities.



### Application

The DNT-T103 is designed to be a low-cost solution for control of unitary equipment. It has built-in, configurable algorithms for VAV, VVT, fan coil/unit ventilator, heat pump, radiation and humidification applications.

The DNT-T103 may also be connected to a LINKnet network to provide programmable remote sensor and expanded I/O capabilities.

### Features

- Native BACnet™ firmware
- BACnet MS/TP
- Configurable 3-value, 96 segment, LCD display (with optional backlighting)
- 4 Configurable push buttons
- Controller firmware can be flash loaded over the network
- Network termination is jumper selectable on each device
- Derived Network Addressing (DNA) for simple integration into a standard network architecture
- Field selectable applications
- Service port

### Specifications

#### BACnet Device Profile

BACnet Application Specific Controller (B-ASC)

#### LCD

3-value and various icons (96 total segments) with optional backlighting

#### Push Buttons

4 stylized momentary push buttons

#### Temperature Sensor

Thermistor Input - 10kΩ at 77°F (25°C)

Accuracy +/-0.36°F from 32-158°F  
(+/- 0.2°C from 0-70°C)

Display resolution of 0.1°

Stability 0.24°F over 5 years (0.13°C)

#### Humidity Sensor

Accuracy of +/- 3%RH from 20% -80% RH  
(linearized accuracy of +/- 3% to +/- 5% from 0-20% and 80-100% RH)

Display Resolution of 0.1%

Stability of < 0.5% RH/yr (typical)

#### Inputs

1 Universal input - 10 bit (supporting 0-5v, 0-10v, 10kΩ)

#### Outputs

3 Binary triac outputs (supporting binary, PWM or tri-state)



#### Technology

32-bit processor with internal A/D, Flash and RAM

Document Edition 3.2 August 2009

## Network Thermostats

### BACstat II: DNT-T103/H103B Board Layout Diagram



#### Specifications (Continued)

##### Device Type

Configured as a LINKnet or subnet device

##### Device Addressing

Set via keypad

##### Communications Ports

BACnet MS/TP @ 9600, 19200, 38400 or 76800 bps (maximum of 99 devices per BACnet MS/TP segment)

##### Connectors

Screw-type terminal connectors

##### Wiring Class

Class 2

##### Power

24V AC

41 VA (with internally powered outputs)

##### Ambient

32° to 104°F (0° to 40°C)

10 - 90% RH (non-condensing)

##### Dimensions

5 x 3.25 x 1 in. (12.7 x 8.3 x 2.5 cm) with housing

0.3 lb. (134 g) with housing

##### Listings

UL 916 Listed

UL 864 Listed (DNT-T103-UL864 only)

BTL Listed

##### Compliance

CE

FCC Class B

#### Accessories

DZNR-768—Delta Network Repeater for BACnet MS/TP

CON-768BT—Delta Network Converter

#### Ordering

Order the DNT-T103/H103 with the desired options, according to the following product numbers:

DNT-T103—Internal Thermistor Input, Additional I/O (1 IP and 3 OP)

DNT-T103BX—Backlighting, External Thermistor Terminator

DNT-T103-UL864—Same as previous, but with UL 864 Listing

DNT-H103B—Internal Thermistor Input, Internal Humidity Input, Additional I/O (1 IP and 3 OP),

Backlighting, External Thermistor Terminator

An appended button icon code must be included to specify the desired icons embossed on the buttons. If a button icon code is not specified, the product is shipped with the default button icons.

Default—Bottom 2 buttons are ▼ & ▲ (Setpoint Adjust), top 2 buttons are OFF and ON

INT—Bottom 2 buttons are ▼ & ▲ (Setpoint Adjust), top 2 buttons are 0 and 1 (International)