



Network Sensors: eZNT-T100

Description

The eZNT-T100 adds an MS/TP network sensor option to the enteliZONE line of sensors and thermostats. The eZNT-T100 gives building occupants an intuitive touch-interface to adjust individual comfort levels while tailoring to the needs of their specific market. Featuring a universal input and a standard temperature sensor with humidity, CO₂ and motion options, the eZNT-T100 also offers a choice of backlit colors to provide additional user feedback and esthetic appeal.

The eZNT NFC technology allows installers to use NFC-enabled mobile devices to configure the sensor on the wall or in its shipped box.



Application

The eZNT-T100 has the same sensing functionality as the eZNS-T100 but instead communicates on an MS/TP network that allows easy integration with other Delta or third-party MS/TP networks. The eZNT-T100 is suitable for a wide range of sensing applications, from basic temperature monitoring, to indoor air quality and occupancy sensing. A customizable interface allows for intuitive user interaction.

The external universal input allows for additional zone monitoring such as window or door contact, external motion sensor for larger rooms, temperature averaging or other local sensor information.

Features

- ▶ Native BACnet® firmware
- ▶ Standard RGB backlight allows choice of colors to indicate conditions, alarms and night mode
- ▶ Large easy-to-read LCD screen. Onscreen visual feedback on button selection
- ▶ Multiple button and slider layout options. Custom button design available through Partner Applications Services (PAS)
- ▶ Support for custom button and screen interactions through GCL+ programming
- ▶ Support for local scheduling, trending and alarming
- ▶ USB Service port, software enabled or disabled. Service tool not required.
- ▶ Smartphone and tablet integration and setup using NFC technology
- ▶ Fits most electrical boxes worldwide
- ▶ 2-piece design with tamper set screw lock

Specifications

Input

1 Universal Input (12-bit), software configurable for:
0-5 VDC
0-10 VDC
10 kΩ Thermistor
Dry Contact

LCD

2-line custom segmented display with icons

Buttons

2 rows of 4 capacitive touch zones, allowing up to 8 individual buttons or combined to form larger buttons

Backlight

RGB LED backlight for multicolor LCD and button illumination

Temperature

Digital Temperature Sensor
+/- 0.2° C (+/- 0.36°F)

Digital Humidity Sensor (Optional)

Accuracy +/- 3%

CO₂ Sensor (Optional)

Dual Beam, Self Calibrating NDIR Detection

Range: 0-2000 ppm

Accuracy @ 25°C (77°F):

± (50ppm + 2% of value)

Temperature Dependence: 2ppm/°C (1 ppm/ °F) typical

Pressure Dependence: 0.13% of reading per mm Hg

Stability: 20 ppm/year (typical)

Occupancy Sensor (Optional)

Passive infrared motion (PIR) sensor

Range: 5m (16.4 ft.)

Coverage: 100° Horizontal

Connectors


Screw-type terminal connectors

Wiring Class


Class 2 / SELV

enteliZONE®

eZNT-T100: Board Layout Diagram



eZNT-T100: Dimensions and Backplate Options



Specifications (Continued)

Power

24 V AC/DC
4 VA / 1.2 W

Communications

RS-485 port
BACnet MS/TP (up to 76800 bps)

USB Service Port

Used as virtual Com port to connect the BACnet® network to a workstation

Near Field Communication (NFC)

Passive 2-way short range

Ambient

0° to 55°C (32° to 131°F)
10 - 90% RH (non-condensing)

Dimensions

With SM backplate:
13.3 x 9.3 x 2.3 cm (5.3 x 3.6 x 0.9 in.)

With SC (CO₂) backplate:
13.3 x 9.3 x 4.3 cm (5.3 x 3.6 x 1.7 in.)

Mounted Surface Profile

Surface Mount (SM, SC backplates):
2.3 cm (0.9 in.)

Weight

175 g (0.39 lbs)

IP Rating

IP20

Compliance

CE
FCC Class B

Listings

UL 916 Listed

Subject to change without notice.

enteliZONE[®]

Ordering

The product number of the eZNT-T100 is eZNT-T100aaa-B-cc-ddd-eee where the letters correspond to the different options listed below:

Sensor Options (aaa-)

C	CO ₂ Only
HM	Humidity and Motion
CHM	CO ₂ , Humidity and Motion

Backlit Display (-B-)

B	RGB Backlit Display / Buttons is a standard feature
----------	---

Backplate Options (-cc-)

SC	CO ₂ ¹
SM	Surface Mount

¹CO₂ sensor options require CO₂ backplate.

Button Overlay Options (-ddd-)

###	Standard Button Overlay Number
###	Library Button Overlay Number ²
999	Custom Button Overlay ³

²See eZNS Button Overlay Design Guide. Expect up to 8 weeks for delivery. Additional charges apply.

Button Overlay and Plastic Color Options (-eee-)

WWG	White Button Overlay, White Front with Grey Backplate (default)
GWG	Grey Button Overlay, White Front with Grey Backplate
BBB	Black Button Overlay, Black Front with Black Backplate
Custom	Custom Color Options ³

³Contact inside sales for pricing and more information.

enteliZONE is a registered trademark of Delta Controls Inc.
BACnet is a registered trademark of the American Society of Heating, Refrigerating and Air Conditioning Engineers Inc.

Updated June 25 2018_r

enteliZONE®

eZNT-T100: Standard Button Overlay Options



Overlay 003



Overlay 005



Overlay 009




Overlay 015



Overlay 027



Overlay 045




Overlay 046



Overlay 047



Overlay 053



Overlay 100

eZNT-T100: Color Options



WWG: White Button Overlay, White Front, Grey Back



GWG: Grey Button Overlay, White Front, Grey Back



BBB: Black Button Overlay, Black Front, Black Back